

Coolers

Bottle / Display Coolers | Can Coolers | Back Bars



BOTTLE display coolers

In this section you will find some of our most popular items. The glass door merchandisers are among our best selling products because of the timeless design and functionality.

Most products in this section are well-suited for branding. Available with glass door or solid door, with or without canopy and in several different sizes, this range offers many combinations. All units are designed to work in a hot environment. For the FS/SCU series matching freezers are available.

Chest Bottle Coolers can also be found in this section, page 60



Did you know?

You can find our eco-friendly bottle cooler GBC - with or without canopy - on pages 34-35.



» Bottle Coolers



BC25CP

- LED light
- Fan assisted cooling
- Glass door
- 2 Fixed shelves
- Adjustable feet



FS60CP

- Illuminated Canopy
- Fan assisted cooling
- Glass door
- 2 Fixed shelves
- Adjustable feet



FSC100

- Illuminated Canopy
- Fan assisted cooling
- Self -Closing Sliding Glass door
- 3 Adjustable shelves
- Brackets for wall-hanging
- Adjustable feet

Technical specifications

Model	BC25CP	FS60CP	FS80CP	FSC100
Climate Class	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	25	60	84	100
Net Volume, l	22	45	55	60
Cans, 330 ml	18	48	114	96
Cans, 500 ml	18	48	84	64
Bottles, 330 ml	-	-	66	64
Bottles, 1,5 l PET	-	-	-	-
External Dimensions, WxDxH	332x423x618	455x440x720	480x460x840	655x390x930
Internal Dimensions, WxDxH	258x270x373	395x270x440	410x380x550	560x265x635
Doors	1 hinged glass	1 hinged glass	1 hinged self closing glass	2 sliding glass
Shelves/Baskets	2	2, 395x265	2, 400x260	3, 560x210
Outer Body	Black/grey	White	White	White
Interior	Aluminium	ABS	ABS	ABS
Castors/Feet	4 adjustable feet	4 adjustabel feet	4 adjustable feet	4 adjustable feet/Wall
Lock	Y	Y	Y	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	75	160	215	220
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	26	37	43	51
Net Weight, kg	23	32,5	37,5	45,5
Noise Level dbA	44	44	42	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N	N
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	50	80	90	115
Internal Light	LED	8 W neon	15 W Neon	15 W Neon
Canopy Light	LED	8 W Neon	15 W Neon	15 W Neon
Option: Charged with R600a				

» Bottle Coolers



BC85 / 145

- Interior LED light
- Curved glass door
- 3 Adjustable shelves
- Adjustable feet



BC30

- LED light
- Fan assisted cooling
- Glass door
- 1 Fixed shelf
- 1 Adjustable shelf
- Adjustable feet



BC60

- LED light
- Fan assisted cooling
- Glass door
- 1 Fixed shelf
- 2 Adjustable shelves
- Adjustable feet

Technical specifications

Model	BC30	BC60	BC85	BC145	BC145 w/fan
Climate Class	N	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to10	2 to10	2 to 10
Gross Volume, l	22	67	92	109	109
Net Volume, l	20	58	85	105	105
Cans, 330 ml	20	20	101	136	136
Cans, 500 ml	55	55	70	89	89
Bottles, 330 ml	-	-	64	76	76
Bottles, 1,5 l PET	-	-	22	27	27
External Dimensions, WxDxH	356x406x491	432x496x668	503x560x775	503x560x850	503x560x850
Internal Dimensions, WxDxH	280x271x380	356x311x557	410x415x630	410x415x710	410x415x710
Doors	1 hinged glass	1 hinged glass	1 curved glass	1 curved glass	1 curved glass
Shelves/Baskets	2	3	3	3	3
Outer Body	Black	Black	White	White	White
Interior	ABS	ABS	ABS	ABS	ABS
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	87	100	75	122	122
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	24,6	35,7	35	38	38
Net Weight, kg	22,2	32,5	33	36	36
Noise Level dbA	44	44	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Static	Static	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	N	N	Digital	Digital	Digital
Refrigerant	R134a	R134a	R134a	R134a	R134a
Charge, g	45	50	80	80	80
Internal Light	LED	LED	LED	LED	LED

» Bottle Coolers



CEV425CP LED DOOR

- Internal LED light in glass door
- Illuminated canopy
- Fan assisted cooling
- Strong handle
- 4 Adjustable shelves
- Adjustable feet



CEV425

- Fan assisted cooling
- Internal light
- Reversible glass door
- 4 Adjustable shelves
- Adjustable feet



CEV425CP

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Reversible glass door
- 4 Adjustable shelves
- Adjustable feet

Technical specifications

Model	CEV425	CEV425CP	CEV425CP LED DOOR
Climate Class	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	374	374	374
Net Volume, l	350	350	350
Cans, 330 ml	455	455	455
Cans, 500 ml	301	301	301
Bottles, 330 ml	217	217	217
Bottles, 0,5 l PET	217	217	217
External Dimensions, WxDxH	595x600x1840	595x600x1880	595x600x1980
Internal Dimensions, WxDxH	523x462x1555	523x436x1555	523x436x1555
Doors	1 glass	1 glass	1 glass
Shelves/Baskets	4, 515x405	4, 515x405	4, 515x405
Outer Body	White	White	White
Interior	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	295	295	295
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	84,9	90,1	90,1
Net Weight, kg	75,5	80,4	80,4
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	200	200	200
Internal Light	15 W Neon	15 W Neon	LED in door
Canopy Light	N	15 W Neon	15 W Neon
Option: Charged with R600a			

» Bottle Coolers



2 doors on model FS2380

- FS1380**
- Fan assisted cooling
 - Internal light
 - Reversible Glass door
 - 5 Adjustable shelves
 - Adjustable feet



- FS1280**
- Fan assisted cooling
 - Internal light
 - Reversible Glass door
 - 4 Adjustable shelves
 - Adjustable feet



- FS1220**
- Fan assisted cooling
 - Internal light
 - Reversible Glass door
 - 3 Adjustable shelves
 - Adjustable feet

Technical specifications

Model	FS1220	FS1280	FS1380	FS2380
Climate Class	N-T	N-T	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	215	290	372	372
Net Volume, l	190	260	345	345
Cans, 330 ml	301	392	455	448
Cans, 500 ml	175	259	301	294
Bottles, 330 ml	133	175	217	210
Bottles, 0,5 l PET	133	175	217	210
External Dimensions, WxDxH	595x600x1315	595x600x1635	595x600x1840	595x600x1840
Internal Dimensions, WxDxH	470x450x887	470x450x1347	470x450x1552	470x450x1552
Doors	1 glass	1 glass	1 glass	2 glass
Shelves/Baskets	3, 490x360	4, 490x360	5, 490x360	5, 490x360
Outer Body	White	White	White	White
Interior	ABS	ABS	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	Y	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	229	266	295	295
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	64,4	79,3	84,9	84,9
Net Weight, kg	56,3	70	75,5	75,5
Noise Level dbA	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	90	180	200	200
Internal Light	15 W Neon	15 W Neon	15 W Neon	15 W Neon
Option: Charged with R600a				

» Bottle Coolers



2 doors on model FSC2380

FSC1380

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Reversible Glass door
- 5 Adjustable shelves
- Adjustable feet



FSC1220

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Reversible Glass door
- 3 Adjustable shelves
- Adjustable feet



FSC1280

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Reversible Glass door
- 4 Adjustable shelves
- Adjustable feet

Technical specifications

Model	FSC1220	FSC1280	FSC1380	FSC2380
Climate Class	N-T	N-T	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	215	290	372	372
Net Volume, l	190	260	345	345
Cans, 330 ml	301	392	455	448
Cans, 500 ml	175	259	301	294
Bottles, 330 ml	133	175	217	210
Bottles, 0,5 l PET	133	175	217	210
External Dimensions, WxDxH	595x600x1455	595x600x1775	595x600x1980	595x600x1980
Internal Dimensions, WxDxH		470x450x1347	470x450x1552	470x450x1552
Doors	1 glass	1 glass	1 glass	1 glass
Shelves/Baskets	3, 490x360	4, 490x360	5, 490x360	5, 490x360
Outer Body	White	White	White	White
Interior	ABS	ABS	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	230	266	295	295
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	71,4	83,3	90,1	90,1
Net Weight, kg	62,5	74	80,4	80,4
Noise Level dbA	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	90	180	200	200
Internal Light	15 W Neon	15 W Neon	15 W Neon	15 W Neon
Canopy Light	15 W Neon	15 W Neon	15 W Neon	15 W Neon
Option: Charged with R600a				

» Bottle Coolers



GBC 375CP

- LED illuminated canopy
- Fan assisted cooling
- Internal LED light
- Reversible glass door
- Strong handle
- 5 Adjustable shelves
- Adjustable feet



GBC 375

- Fan assisted cooling
- Internal LED light
- Reversible glass door
- Strong handle
- 5 Adjustable shelves
- Adjustable feet



Strong handle

Technical specifications

	GBC 375	GBC 375CP
Climate Class	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10
Gross Volume, l	372	372
Net Volume, l	347	347
Cans, 330 ml	455	455
Cans, 500 ml	301	301
Bottles, 330 ml	217	217
Bottles, 0,5 l PET	217	217
External Dimensions, WxDxH	595x600x1840	595x600x1980
Internal Dimensions, WxDxH	470x450x1552	470x450x1552
Doors	1 glass	1 glass
Shelves/Baskets	5	5
Outer Body	White	White
Interior	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50
Input Power, W	295	295
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	85	91
Net Weight, kg	76	82
Noise Level dbA	40	40
Type of Cooling	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic
Controller	Mechanical	Mechanical
Thermometer	Y	Y
Refrigerant	R600a	R600a
Charge, g	80	80
Internal Light	LED	LED
Canopy Light	-	LED

» Bottle Coolers



FSC1380CURVED

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Curved Glass door
- Integrated handle
- 5 Adjustable shelves
- Adjustable feet



FSC1450

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Glass door
- 5 Adjustable shelves
- Adjustable feet



SCU1450CP

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Glass door
- 5 Adjustable shelves
- Adjustable feet

Technical specifications

Model	FSC1380CURV	FSC1450	SCU1450CP
Climate Class	N-T	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	380	438	438
Net Volume, l	347	374	374
Cans, 330 ml	455	720	720
Cans, 500 ml	301	486	486
Bottles, 330 ml	217	360	360
Bottles, 0,5 l PET	217	360	360
External Dimensions, WxDxH	595x625x1980	680x655x2090	680x655x2090
Internal Dimensions, WxDxH	470x450x1552	585x495x1515	585x495x1515
Doors	1 glass	1 glass	1 glass
Shelves/Baskets	5, 495x448	5, 574x405	5, 574x405
Outer Body	White	White	White
Interior	ABS	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	352	350	350
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	98	105	105
Net Weight, kg	90	97	97
Noise Level dbA	45	49	49
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	200	200	200
Internal Light	15 W Neon	36 W Neon	36 W Neon
Canopy Light	15 W Neon	18 W Neon	18 W Neon
Option: Charged with R600a			

» Bottle Coolers



2 doors on model SCU2375

SCU1375

- Fan assisted cooling
- Internal light
- Reversible Glass door
- 5 Adjustable shelves
- Adjustable feet



SCU1220

- Fan assisted cooling
- Internal light
- Reversible Glass door
- 3 Adjustable shelves
- Adjustable feet



SCU1280

- Fan assisted cooling
- Internal light
- Reversible Glass door
- 4 Adjustable shelves
- Adjustable feet

Technical specifications

Model	SCU1220	SCU1280	SCU1375	SCU2375
Climate Class	N-T	N-T	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	215	290	372	372
Net Volume, l	190	260	345	345
Cans, 330 ml	301	392	455	448
Cans, 500 ml	175	259	301	294
Bottles, 330 ml	133	175	217	210
Bottles, 0,5 l PET	133	175	217	210
External Dimensions, WxDxH	595x600x1315	595x600x1635	595x600x1840	595x600x1840
Internal Dimensions, WxDxH	470x450x1025	470x450x1347	470x450x1552	470x450x1552
Doors	1 glass	1 glass	1 glass	2 glass
Shelves/Baskets	3, 490x360	4, 490x360	5, 490x360	5, 490x360
Outer Body	White	White	White	White
Interior	ABS	ABS	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	Y	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	229	266	295	295
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	64,4	79,3	84,9	84,9
Net Weight, kg	56,3	70	75,5	75,5
Noise Level dbA	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	90	180	200	200
Internal Light	15 W Neon	15 W Neon	15 W Neon	15 W Neon
Option: Charged with R600a				

» Bottle Coolers



2 doors on model SCU2375CP

SCU1375CP

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Reversible Glass door
- 5 Adjustable shelves
- Adjustable feet



SCU1220CP

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Reversible Glass door
- 3 Adjustable shelves
- Adjustable feet



SCU1280CP

- Illuminated canopy
- Fan assisted cooling
- Internal light
- Reversible Glass door
- 4 Adjustable shelves
- Adjustable feet

Technical specifications

Model	SCU1220CP	SCU1280CP	SCU1375CP	SCU2375CP
Climate Class	N-T	N-T	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	215	290	372	372
Net Volume, l	190	260	345	345
Cans, 330 ml	301	392	455	448
Cans, 500 ml	175	259	301	294
Bottles, 330 ml	133	175	217	210
Bottles, 0,5 l PET	133	175	217	210
External Dimensions, WxDxH	595x600x1455	595x600x1775	595x600x1980	595x600x1980
Internal Dimensions, WxDxH	470x450x1025	470x450x1347	470x450x1552	470x450x1552
Doors	1 glass	1 glass	1 glass	1 glass
Shelves/Baskets	3, 490x360	4, 490x360	5, 490x360	5, 490x360
Outer Body	White	White	White	White
Interior	ABS	ABS	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	230	266	295	295
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	71,4	83,3	90,1	90,1
Net Weight, kg	62,5	74	80,4	80,4
Noise Level dbA	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	90	180	200	200
Internal Light	15 W Neon	15 W Neon	15 W Neon	15 W Neon
Canopy Light	15 W Neon	15 W Neon	15 W Neon	15 W Neon
Option: Charged with R600a				

» Bottle Coolers



FSC1450 Sub Zero

- Electronic thermostat
- Illuminated canopy
- Fan assisted cooling
- Internal light
- 5 Adjustable shelves
- Adjustable feet



FS80CP Sub Zero

- Electronic thermostat
- Illuminated canopy
- Fan assisted cooling
- Self -Closing heated glass door
- 2 Adjustable shelves
- Adjustable feet

Technical specifications

Model	FS80CP/SUB ZERO	FSC1380/SUB ZERO	FSC1450/SUB ZERO
Climate Class	N-T	N-T	N-T
Temperature Range, °C	-2,5 to 5	-2,5 to 5	-2,5 to 5
Gross Volume, l	84	372	438
Net Volume, l	55	345	374
Cans, 330 ml	60	364	480
Cans, 500 ml	40	196	324
Bottles, 330 ml	48	161	272
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	480x460x840	595x600x1980	680x655x2090
Internal Dimensions, WxDxH	-	470x450x1552	585x495x1515
Doors	1 hinged self-closing glass	1 glass	1 glass
Shelves/Baskets	2, 400x260	5, 490x360	5, 574x405
Outer Body	White	White	White
Interior	ABS	ABS	ABS
Castors/Feet	4 adjustable feet	2 rollers and 2 feet	2 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	255	295	427
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	43	90,1	105
Net Weight, kg	37,5	80,4	97
Noise Level dbA	42	45	49
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Electronic	Electronic	Electronic
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	90	200	200
Internal Light	15 W Neon	15 W Neon	36 W Neon
Canopy Light	15 W Neon	15 W Neon	18 W Neon

» Display Coolers



FS1200S Digital

- Electronic thermostat
- Internal vertically light
- Ventilated cooling
- 2 sliding glass doors
- 4 Adjustable shelves
- Adjustable feet



FSC1000S

- Illuminated canopy
- Internal vertically light
- Ventilated cooling
- 2 sliding glass doors
- 1 Bottom shelf
- 4 Adjustable shelves
- Adjustable feet



FSC1200S

- Illuminated canopy
- Internal vertically light
- Ventilated cooling
- 2 sliding glass doors
- 1 Bottom shelf
- 4 Adjustable shelves
- Adjustable feet

Technical specifications

Model	FS1000S Digital	FS1200S Digital	FSC900S	FSC1000S	FSC1200S
Climate Class	N-T	N-T	N-T	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	800	980	723	771	945
Net Volume, l	720	882	648	691	847
Cans, 330 ml	1196	1472	-	1144	1408
Cans, 500 ml	754	928	-	728	896
Bottles, 330 ml	546	672	-	520	640
Bottles, 0,5 l PET	546	672	-	520	640
External Dimensions, WxDxH	1000x735x2010	1200x735x2010	900x740x2010	1000x740x2010	1200x740x2010
Internal Dimensions, WxDxH	890x578x1555	1090x578x1555	820x572x1533	890x572x1533	1090x572x1533
Doors	2 sliding glass	2 sliding glass	2 sliding glass	2 sliding glass	2 sliding glass
Shelves/Baskets	5, 870x475	5, 1070x475	5	5	5
Outer Body	White	White	White	White	White
Interior	Powder coated	Powder coated	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 rollers	4 rollers	4 rollers	4 rollers	4 rollers
Lock	N	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	670	740	-	700	850
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	176	189	-	175	188,5
Net Weight, kg	163	174	-	162	174
Noise Level dbA	48	48	48	48	48
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic	Automatic
Controller	Electronic	Electronic	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R290	R134a	R134a
Charge, g	450	460	-	450	450
Internal Light	36 W Neon	36 W Neon	-	36 W Neon	36 W Neon
Canopy Light	N	N	-	30 W Neon	30 W Neon

» Display Coolers



FSC900H, 900 mm. wide available primo 2016

FSC1000H

- Internal vertically light
- Ventilated cooling
- 2 hinged glass doors
- 1 Bottom shelf
- 4 Adjustable shelves
- Adjustable feet



FSC1200H

- Illuminated canopy
- Internal vertically light
- Ventilated cooling
- 2 hinged glass doors
- 1 Bottom shelf
- 4 Adjustable shelves
- Adjustable feet



FSC1950S

- Illuminated canopy
- Internal vertically light
- Ventilated cooling
- 2 sliding glass doors
- 1 Bottom shelf
- 4 Adjustable shelves
- Adjustable feet

Technical specifications

Model	FSC1000H	FSC1200H	FSC1950H	FSC1950S
Climate Class	N-T	N-T	N-T	N-T
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	796	970	1013	988
Net Volume, l	696	852	871	866
Cans, 330 ml	1287	1584	1020	1020
Cans, 500 ml	819	1008	720	720
Bottles, 330 ml	585	720	560	560
Bottles, 0,5 l PET	585	720	560	560
External Dimensions, WxDxH	1000x790x2010	1200x790x2010	1110x825x2025	1110x825x2025
Internal Dimensions, WxDxH	890x670x1533	1090x670x1533	1000x645x1530	1000x645x1530
Doors	2 hinged glass	2 hinged glass	2 hinged glass	2 sliding glass
Shelves/Baskets	5	5	5	5
Outer Body	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 rollers	4 rollers	4 rollers	4 rollers
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	700	850	817	817
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	175	188,5	195	195
Net Weight, kg	162	174	175	175
Noise Level dbA	48	48	55	55
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	450	450	900	900
Internal Light	36 W Neon	36 W Neon	30 W Neon	30 W Neon
Canopy Light	30 W Neon	30 W Neon	30 W Neon	30 W Neon

» Display Coolers



SLDG800

- Illuminated canopy
- Internal vertically light
- Fan assisted cooling
- 2 sliding glass doors
- 5 Adjustable shelves behind each door
- Adjustable feet



SLDG600

- Illuminated canopy
- Internal vertically light
- Fan assisted cooling
- 2 sliding glass doors
- 5 Adjustable shelves behind each door
- Adjustable feet



SLDG1000

- Illuminated canopy
- Internal vertically light
- Fan assisted cooling
- 2 sliding glass doors
- 5 Adjustable shelves behind each door
- Adjustable feet

Technical specifications

Model	SLDG600	SLDG725	SLDG800	SLDG1000
Climate Class	N-T	N-T	N-T	N-T
Temperature Range, °C	2 to 12	2 to 12	2 to 12	2 to 12
Gross Volume, l	593	720	786	937
Net Volume, l	576	673	776	914
Cans, 330 ml	560	655	752	848
Cans, 500 ml	-	-	-	-
Bottles, 330 ml	360	360	476	612
Bottles, 0,5 l PET	360	360	476	612
External Dimensions, WxDxH	890x630x2035	1000x630x2035	1140x630x2035	1360x630x2035
Internal Dimensions, WxDxH	800x500x1440	910x500x1440	1050x500x1440	1270x500x1440
Doors	2 sliding glass	2 sliding glass	2 sliding glass	2 sliding glass
Shelves/Baskets	10, 470x378	10, 470x435	10, 490x485	10, 625x485
Outer Body	White	White	White	White
Interior	Powder coated	Powder coated	Powder coated	Powder coated
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	N, Option	N, Option	N, Option	N, Option
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	590	590	590	1000
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	163	202	203	234
Net Weight, kg	155	194	195	225
Noise Level dbA	50	50	50	50
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	320	325	360	380
Internal Light	36 W Neon	36 W Neon	36 W Neon	36 W Neon
Canopy Light	18 W Neon	18 W Neon	30 W Neon	30 W Neon

» Bottle Coolers



SD1380

- Fan assisted cooling
- Reversible Solid door
- 5 Adjustable shelves
- Adjustable feet



SD1220

- Fan assisted cooling
- Reversible Solid door
- 3 Adjustable shelves
- Adjustable feet



SD1280

- Fan assisted cooling
- Reversible Solid door
- 4 Adjustable shelves
- Adjustable feet

Technical specifications

Model	SD1220	SD1280	SD1380
Climate Class	N-T	N-T	N-T
Temperature Range, °C	2 to 12	2 to 12	2 to 12
Gross Volume, l	215	290	372
Net Volume, l	190	260	345
Cans, 330 ml	301	392	455
Cans, 500 ml	175	259	301
Bottles, 330 ml	133	175	217
Bottles, 0,5 l PET	133	175	217
External Dimensions, WxDxH	595x600x1315	595x600x1635	595x600x1840
Internal Dimensions, WxDxH	470x440x1020	470x440x1340	470x440x1545
Doors	1 solid	1 solid	1 solid
Shelves/Baskets	3, 490x360	4, 490x360	5, 490x360
Outer Body	White	White	White
Interior	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	175	185	215
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	74	85	94
Net Weight, kg	63	78	86
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	90	180	200
Internal Light	N	N	N
Option: Charged with R600a			

» Bottle Coolers



SDU1220

- Fan assisted cooling
- Reversible Solid door
- 3 Adjustable shelves
- Adjustable feet



SDU1280

- Fan assisted cooling
- Reversible Solid door
- 4 Adjustable shelves
- Adjustable feet



SDU1375

- Fan assisted cooling
- Reversible Solid door
- 5 Adjustable shelves
- Adjustable feet

Technical specifications

Model	SDU1220	SDU1280	SDU1375
Climate Class	N-T	N-T	N-T
Temperature Range, °C	2 to 12	2 to 12	2 to 12
Gross Volume, l	215	290	372
Net Volume, l	190	260	345
Cans, 330 ml	301	392	455
Cans, 500 ml	175	259	301
Bottles, 330 ml	133	175	217
Bottles, 0,5 l PET	133	175	217
External Dimensions, WxDxH	595x640x1315	595x640x1635	595x640x1840
Internal Dimensions, WxDxH	470x440x1020	470x440x1340	470x440x1545
Doors	1 solid	1 solid	1 solid
Shelves/Baskets	3, 490x360	4, 490x360	5, 490x360
Outer Body	White	White	White
Interior	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	185	215	175
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	85	94	74
Net Weight, kg	78	86	63
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	90	180	200
Internal Light	N	N	N
Option: Charged with R600a			

» Upright Coolers



UR200SG

- Stainless steel cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 3 adjustable shelves
- Adjustable feet at front, rollers at back
- Digital thermometer
- Option: Wheels or adjustable legs



UR200G

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 3 adjustable shelves
- Adjustable feet at front, rollers at back
- Digital thermometer
- Option: Wheels or adjustable legs



UR400G

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 adjustable shelves
- Adjustable feet at front, rollers at back
- Digital thermometer
- Option: Wheels or adjustable legs

Technical specifications

Model	UR200G	UR200SG	UR400G	UR400SG
Climate Class	N	N	N	N
Temperature Range, °C	0 to 10	0 to 10	0 to 10	0 to 10
Gross Volume, l	130	130	374	374
Net Volume, l	119	119	350	350
External Dimensions, WxDxH	600x600x850	600x600x850	600x600x1850	600x600x1850
Internal Dimensions, WxDxH	510x485x620	510x485x620	510x485x1620	510x485x1620
Doors	1 hinged glass	1 hinged glass	1 hinged glass	1 hinged glass
Shelves/Baskets	3	3	4	4
Outer Body	White	SS430	White	SS430
Interior	ABS	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	130	130	185	185
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	59	59	94	94
Net Weight, kg	54	54	89	89
Noise Level dbA	40	40	40	40
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	75	75	170	170
Internal Light	LED	LED	LED	LED
Option: Charged with R600a				

» Upright Coolers



Fan assisted cooling

UR200S

- Stainless steel cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 3 Adjustable shelves
- Adjustable feet at front, rollers at back
- Fan assisted cooling
- Automatic defrost
- Digital thermometer
- Option: Wheels or adjustable legs



UR400

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 Adjustable shelves
- Adjustable feet at front, rollers at back
- Fan assisted cooling
- Automatic defrost
- Digital thermometer
- Option: Wheels or adjustable legs



UR600

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 Adjustable shelves GN2/1
- Adjustable feet at front, rollers at back
- Fan assisted cooling
- Automatic defrost
- Digital thermometer
- Option: Wheels or adjustable legs

Technical specifications

Model	UR200	UR200S	UR400	UR400S	UR600	UR600S
Climate Class	N-T	N-T	N-T	N-T	N-T	N-T
Temperature Range, °C	0 to 10	0 to 10	0 to 10	0 to 10	0 to 10	0 to 10
Gross Volume, l	130	130	374	374	599	599
Net Volume, l	119	119	350	350	570	570
Cans, 330 ml	-	-	-	-	-	-
Cans, 500 ml	-	-	-	-	-	-
Bottles, 330 ml	-	-	-	-	-	-
Bottles, 1,5 l PET	-	-	-	-	-	-
External Dimensions, WxDxH	600x600x850	600x600x850	600x600x1850	600x600x1850	770x750x1900	770x750x1900
Internal Dimensions, WxDxH	-	-	-	-	-	-
Doors	1 solid White	1 solid SS430	1 solid White	1 solid SS430	1 solid White	1 solid SS430
Shelves/Baskets	2, 502x440 and 1, 502x211	2, 502x440 and 1, 502x211	3, 502x440 and 1, 502x211	3, 502x440 and 1, 502x211	3, GN2/1 and 1, 650x305	3, GN2/1 and 1, 650x305
Outer Body	White	SS430	White	SS430	White	SS430
Interior	ABS	ABS	ABS	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	150	150	185	185	200	200
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	49	49	74	74	97	97
Net Weight, kg	44	44	69	69	90	90
Noise Level dbA	40	40	40	40	40	40
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a
Charge, g	75	75	170	170	210	210
Internal Light	N	N	N	N	N	N
Option: Charged with R600a						

» Chest Bottle Coolers



USS300YSC Chest Bottle Cooler

- Sliding glass lids
- Lock
- Double wheels
- Suitable for branding with stickers
- Options: Available with copper evaporator



USS300SD Chest Bottle Cooler

- Solid, sliding lids
- Integrated handle
- Strong wheels
- Suitable for branding with stickers
- Options: Available with copper evaporator



USS300Y

- Flip-Flop solid lids
- Inner liner of stucco aluminium
- 4 castors included
- Options: Available with copper evaporator

Technical specifications

Model	USS300SD	USS300Y	USS300YSC
Climate Class	N-T	N-T	N-T
Temperature Range, °C	1 to 10	-6 to 10	-6 to 10
Gross Volume, l	296	289	296
Net Volume, l	261	283	261
Cans, 330 ml	400	413	400
Cans, 500 ml	245	245	245
Bottles, 330 ml	245	245	245
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	1020x640x860	1060x670x825	1020x640x860
Internal Dimensions, WxDxH	890x510x663	890x510x682	890x510x663
Doors	2 sliding solid	Flip-Flop solid	2 sliding glass
Shelves/Baskets	-	-	-
Outer Body	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 wheels	4 wheels	4 wheels
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	240	250	240
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	60	63	60
Net Weight, kg	53	57	53
Noise Level dbA	42	42	42
Type of Cooling	Static	Static	Static
Type of Defrost	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N
Refrigerant	R134a	R134a	R134a
Charge, g	260	260	260
Internal Light	N	N	N



CAN impulse coolers

For increasing the number of impulse sales, we offer can coolers as well as impulse chillers well suited for branding, with a stylish shape that will certainly attract customers.

These mobile products are suitable for shops or for self-service drinks at parties.

The internal fan ensures a fast and even cooling of the beverage and the internal baskets make it easy to load and unload them.



Did you know?

Please consider how the high quality of the cooler reflects the high quality of the product inside.

» Can Coolers



VOC75

- Illuminated canopy
- Internal fan
- Internal baskets
- Fast pull-down of temperature
- Well suited for graphics
- 4 strong castors



VOC100

- Designed for canned drinks
- Illuminated light-board
- Internal fan
- Fast pull-down of temperature
- Well suited for graphics
- 7 sliding shoes



VOC70

- Illuminated canopy
- Internal fan
- Internal baskets
- Fast pull-down of temperature
- Well suited for graphics
- 4 strong castors

Technical specifications

Model	VOC70	VOC75	VOC100
Climate Class, N,SN,ST,T	N	N	N
Temperature Range, °C	2 to 12	2 to 12	2 to 12
Gross Volume, l	65	65	110
Net Volume, l	57	57	103
Cans, 330 ml	78	78	-
Cans, 500 ml	36	36	-
Bottles, 330 ml	-	-	-
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	Ø570x980	Ø570x980	660x460x970
Internal Dimensions, WxDxH	Ø470x310	Ø470x310	520x320x570
Doors	N	N	N
Shelves/Baskets	N	N	N
Outer Body	White	White	RAL9006
Interior	Powder coated	Powder coated	SAC
Castors/Feet	4 castors	4 castors	7 sliding shoes
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	211	211	140
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	37	37	31
Net Weight, kg	32	32	29
Noise Level dbA	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Electronic
Thermometer	N	N	Y
Refrigerant	R134a	R134a	R134a
Charge, g	100	100	151
Internal Light	N	N	N
Canopy Light	8 W neon	8 W neon	LED
Option: Charged with R600a			

» Can Coolers



Available in white



Internal fan and basket

CC77 w/Fan BLACK

- Designed for canned drinks
- Internal fan
- Fast pull-down of temperature
- Internal basket
- Flip-flop lid
- Well suited for graphics
- 4 strong castors



CC45 w/Fan

- Designed for canned drinks
- Internal fan
- Fast pull-down of temperature
- Internal basket
- Flip-flop lid
- Well suited for graphics
- 4 strong castors



CC55 w/Fan

- Designed for energy drinks
- Internal fan
- Fast pull-down of temperature
- Internal baskets
- Flip-flop lid
- Well suited for graphics
- 4 strong castors

Technical specifications

Model	CC45 w/Fan	CC55 w/Fan	CC77 w/Fan	CC77 w/Fan BLACK
Climate Class	N	N	N	N
Temperature Range, °C	0 to 8	0 to 8	0 to 8	0 to 8
Gross Volume, l	53	80	80	80
Net Volume, l	50	78	77	77
Cans, 330 ml	44	84	78	78
Cans, 500 ml	-	42	36	36
Bottles, 330 ml	-	-	-	-
Bottles, 1,5 l PET	-	-	-	-
External Dimensions, WxDxH	Ø457x830	Ø457x1076	Ø567x830	Ø567x830
Internal Dimensions, WxDxH	Ø375x470	Ø380x655	Ø450x475	Ø450x475
Doors	Acrylic flip	Acrylic flip	Acrylic flip	Acrylic flip
Shelves/Baskets	1 basket	2 baskets	1 basket	1 basket
Outer Body	Black	White	White	Black
Interior	Powder coated	Powder coated	Powder coated	Powder coated
Castors/Feet	4 castors, 1 lockable	4 castors, 1 lockable	4 castors, 1 lockable	4 castors, 1 lockable
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	103	112	112	112
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	25	32,5	34	34
Net Weight, kg	22	27,5	29	29
Noise Level dbA	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N	N
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	60	80	95	95
Internal Light	N	N	N	N



BACK BARS

counter chillers

The elegant design of both back bar display and counter chillers makes them suitable for most bars and/or restaurants and the cabinets and counters can easily be combined with each other.



Did you know?

Our backbars are offered with both 87 and 90 cm height, with sliding or hinged doors and with different door frames and innerliners.

» Back Bars



BA-ALU Models with aluminium door frames,
BA-S/A Models with stainless steel body and
aluminium door frame



All Models available with mirror polished
stainless steel interior

BA5H

- Interior LED light
- Fan assisted cooling
- Double glazed door
- 2 Adjustable shelves
- Adjustable feet



BA15H S/A

- SS430 stainless steel exterior
- Aluminium door frame
- Interior LED light
- Fan assisted cooling
- Double glazed door
- 2 Adjustable shelves



BA25H ALU

- Aluminium door frames
- Interior LED light
- Fan assisted cooling
- Double glazed doors
- 2 Adjustable shelves
- Adjustable feet

Technical specifications

Model	BA5H	BA15H	BA25H	BA25S
Climate Class	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	100	122	191	191
Net Volume, l	94	116	183	183
Cans, 330 ml	138	161	270	240
Cans, 500 ml	96	112	188	168
Bottles, 330 ml	-	-	-	-
Bottles, 1,5 l PET	-	-	-	-
External Dimensions, WxDxH	500x520x870	600x520x870	900x520x870	900x515x870
Internal Dimensions, WxDxH	410x350x720	510x350x720	810x350x720	810x350x720
Doors	1 hinged glass	1 hinged glass	2 sliding glass	2 sliding glass
Shelves/Baskets	2, 398x335	2, 498x335	4, 330x395	4, 330x395
Outer Body	Black or SS430	Black or SS430	Black or SS430	Black or SS430
Interior	Stucco Alu. or Mirror steel	Stucco Alu. or Mirror steel	Stucco Alu. or Mirror steel	Stucco Alu. or Mirror steel
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	210	210	230	230
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	46	48	66,4	66,4
Net Weight, kg	44	46	64,4	64,4
Noise Level dbA	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N	N
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	76	76	140	140
Internal Light	LED	LED	LED	LED
Option: Charged with R600a				

» Back Bars



BA20S

- Interior LED light
- Fan assisted cooling
- Double glazed doors
- 4 Adjustable shelves
- Adjustable feet



BA30S-2

- Interior LED light
- Fan assisted cooling
- 2 Double glazed doors
- 2 Adjustable shelves behind each door
- Door holders for easier loading of cabinet
- Adjustable feet



BA30S-3

- Interior LED light
- Fan assisted cooling
- 3 Double glazed doors
- 2 Adjustable shelves behind each door
- Door holders for easier loading of cabinet
- Adjustable feet

Technical specifications

Model	BA20S	BA30S-2	BA30S-3
Climate Class	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	196	328	328
Net Volume, l	188	320	320
Cans, 330 ml	240	380	380
Cans, 500 ml	168	266	266
Bottles, 330 ml	156	240	240
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	900x515x900	1355x515x900	1355x515x900
Internal Dimensions, WxDxH	805x345x730	1257x345x730	1257x345x730
Doors	2 sliding glass	2 sliding glass	3 sliding glass
Shelves/Baskets	4, 330x395	4, 405x365	6, 405x365
Outer Body	Black	Black	Black
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	230	260	260
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	67,4	94	95
Net Weight, kg	65,4	91	92
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N
Refrigerant	R134a	R134a	R134a
Charge, g	140	186	186
Internal Light	LED	LED	LED
Option: Charged with R600a			



BA-S/A Models with stainless steel body and aluminium door frame



BA-ALU Models with aluminium door frames



All Models available with mirror polished stainless steel interior



» Back Bars



BA10H

- Interior LED light
- Fan assisted cooling
- Double glazed door
- 2 Adjustable shelves
- Adjustable feet



BA-ALU Models with aluminium door frames,
BA-S/A Models with stainless steel body and
aluminium door frame



BA-HSD Models with solid doors



All Models available with mirror polished stainless
steel interior



BA20H

- Interior LED light
- Fan assisted cooling
- Double glazed doors
- 4 Adjustable shelves
- Adjustable feet



BA30H

- Interior LED light
- Fan assisted cooling
- 3 Double glazed doors
- 2 Adjustable shelves behind each door
- Adjustable feet

Technical specifications

Model	BA10H	BA20H	BA30H
Climate Class	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	124	196	328
Net Volume, l	118	188	320
Cans, 330 ml	161	270	425
Cans, 500 ml	112	188	296
Bottles, 330 ml	96	156	240
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	600x520x900	900x520x900	1355x520x900
Internal Dimensions, WxDxH	508x355x732	805x345x730	1257x345x730
Doors	1 hinged glass	2 hinged glass	3 hinged glass
Shelves/Baskets	2, 496x350	4, 330x395	6, 405x365
Outer Body	Black	Black	Black
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	210	230	260
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	49	67,4	94,6
Net Weight, kg	47	65,4	91,6
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N
Refrigerant	R134a	R134a	R134a
Charge, g	76	140	186
Internal Light	LED	LED	LED
Option: Charged with R600a			

» Back Bars



DB125H

- Interior LED light
- Fan assisted cooling
- Double glazed door
- ABS door frame
- 2 Adjustable shelves
- Adjustable feet



DB200H

- Fan assisted cooling
- 2 hinged doors
- 4 Adjustable shelves
- Adjustable feet



DB300S-3

- Fan assisted cooling
- 3 sliding doors
- 6 Adjustable shelves
- Adjustable feet

Technical specifications

Model	DB125H	DB200H	DB300H	DB200S	DB300S-3
Climate Class	N	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	122	191	322	191	300
Net Volume, l	116	183	314	183	278
Cans, 330 ml	161	270	380	240	380
Cans, 500 ml	112	188	266	168	266
Bottles, 330 ml	-	-	-	-	-
Bottles, 1,5 l PET	-	-	-	-	-
External Dimensions, WxDxH	600x520x870	900x520x870	1355x520x870	900x515x870	1355x515x870
Internal Dimensions, WxDxH	510x350x720	810x350x720	1257x350x720	810x350x720	1257x345x720
Doors	1 hinged glass	2 hinged glass	3 hinged glass	2 sliding glass	3 sliding glass
Shelves/Baskets	2, 498x335	4, 395x330	6, 430x317	4, 395x330	6, 405x365
Outer Body	Black	Black	Black	Black	Black
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	210	230	260	230	260
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	55	69	97	69	97
Net Weight, kg	53	65	92	65	88
Noise Level dbA	45	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N	N	N
Refrigerant	R600a	R600a	R134a	R600a	R600a
Charge, g	55	165	186	65	90
Internal Light	LED	LED	LED	LED	LED

» Counter Bottle Coolers



CBC210G

- Fan assisted cooling
- 2 Glass doors
- Stainless steel interior
- 4 Adjustable stainless steel shelves
- Adjustable feet



Stainless steel shelves



CBC310G

- Internal LED light
- Fan assisted cooling
- 3 Glass doors
- Stainless steel interior
- 6 Adjustable stainless steel shelves
- Adjustable feet



CBC410G

- Internal LED light
- Fan assisted cooling
- 4 Glass doors
- Stainless steel interior
- 8 Adjustable stainless steel shelves
- Adjustable feet

Technical specifications

Model	CBC210G	CBC310G	CBC410G
Climate Class	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	290	460	630
Net Volume, l	277	442	605
Cans, 330 ml	-	-	-
Cans, 500 ml	-	-	-
Bottles, 330 ml	-	-	-
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	1462x513x860	2002x513x860	2542x513x860
Internal Dimensions, WxDxH	1082x415x760	1622x415x760	2162x415x760
Doors	2 hinged glass	3 hinged glass	4 hinged glass
Shelves/Baskets	4, SS304	6, SS304	8, SS304
Outer Body	Black, RAL9011	Black, RAL9011	Black, RAL9011
Interior	SS430	SS430	SS430
Castors/Feet	6 adjustable feet	8 adjustable feet	10 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	250	250	350
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	135	161	196
Net Weight, kg	130	156	191
Noise Level dbA	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	150	160	190
Internal Light	LED	LED	LED

» Counter Bottle Coolers



CBC220

- Fan assisted cooling
- 1 Solid door
- 2 Drawers
- Stainless steel interior
- 2 Adjustable stainless steel shelves
- Adjustable feet



Combinations of drawers and doors are easily made as doors and drawers are provided as separate kits



CBC210

- Fan assisted cooling
- 2 Solid doors
- Stainless steel interior
- 4 Adjustable stainless steel shelves
- Adjustable feet



CBC240

- Fan assisted cooling
- 4 Drawers
- Stainless steel interior
- Adjustable feet

Technical specifications

Model	CBC210	CBC220	CBC240
Climate Class	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	290	290	290
Net Volume, l	277	277	277
Cans, 330 ml	-	-	-
Cans, 500 ml	-	-	-
Bottles, 330 ml	-	-	-
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	1462x513x860	1462x513x860	1462x513x860
Internal Dimensions, WxDxH	1082x415x760	1082x415x760	1082x415x760
Doors	2 hinged solid	1 door, 2 drawers	4 drawers
Shelves/Baskets	4, SS304	2, SS304	0
Outer Body	Black, RAL9011	Black, RAL9011	Black, RAL9011
Interior	SS430	SS430	SS430
Castors/Feet	6 adjustable feet	6 adjustable feet	6 adjustable feet
Lock	Y	Y	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	250	250	250
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	123	128	133
Net Weight, kg	118	123	128
Noise Level dbA	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	150	150	150
Internal Light	LED	LED	LED

» Counter Bottle Coolers



- CBC320
- Internal LED light
 - Fan assisted cooling
 - 2 Solid doors
 - 2 Drawers
 - Stainless steel interior
 - 6 Adjustable stainless steel shelves
 - Adjustable feet



- CBC310
- Fan assisted cooling
 - Solid doors
 - Stainless steel interior
 - 6 Adjustable stainless steel shelves
 - Adjustable feet



- CBC360
- Internal LED light
 - Fan assisted cooling
 - 6 Drawers
 - Stainless steel interior
 - Adjustable feet

Technical specifications

Model	CBC310	CBC320	CBC340	CBC360
Climate Class	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	460	460	460	460
Net Volume, l	442	442	442	442
Cans, 330 ml	-	-	-	-
Cans, 500 ml	-	-	-	-
Bottles, 330 ml	-	-	-	-
Bottles, 1,5 l PET	-	-	-	-
External Dimensions, WxDxH	2002X513X860	2002X513X860	2002X513X860	2002X513X860
Internal Dimensions, WxDxH	1622X415X760	1622X415X760	1622X415X760	1622X415X760
Doors	3 hinged solid	2 doors, 2 drawers	1 door, 4 drawers	6 drawers
Shelves/Baskets	6, SS304	4, SS304	2, SS304	0
Outer Body	Black, RAL9011	Black, RAL9011	Black, RAL9011	Black, RAL9011
Interior	SS430	SS430	SS430	SS430
Castors/Feet	8 adjustable feet	8 adjustable feet	8 adjustable feet	8 adjustable feet
Lock	Y	Y	Y	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	250	250	250	250
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	143	148	153	158
Net Weight, kg	138	143	148	153
Noise Level dbA	42	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	160	160	160	160
Internal Light	LED	LED	LED	LED

» Counter Bottle Coolers



- CBC440
- Internal LED light
 - Fan assisted cooling
 - 2 Solid doors
 - 4 Drawers
 - Stainless steel interior
 - 4 Adjustable stainless steel shelves
 - Adjustable feet



- CBC410
- Internal LED light
 - Fan assisted cooling
 - 4 Solid doors
 - Stainless steel interior
 - 8 Adjustable stainless steel shelves
 - Adjustable feet



- CBC480
- Internal LED light
 - Fan assisted cooling
 - 8 Drawers
 - Stainless steel interior
 - Adjustable feet

Technical specifications

Model	CBC410	CBC420	CBC440	CBC460	CBC480
Climate Class	N	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	630	630	630	630	630
Net Volume, l	605	605	605	605	605
Cans, 330 ml	-	-	-	-	-
Cans, 500 ml	-	-	-	-	-
Bottles, 330 ml	-	-	-	-	-
Bottles, 1,5 l PET	-	-	-	-	-
External Dimensions, WxDxH	2542x513x860	2542x513x860	2542x513x860	2542x513x860	2542x513x860
Internal Dimensions, WxDxH	2162x415x760	2162x415x760	2162x415x760	2162x415x760	2162x415x760
Doors	4 hinged solid	3 doors, 2 drawers	2 doors, 4 drawers	1 door, 6 drawers	8 drawers
Shelves/Baskets	8, SS304	6, SS304	4, SS304	2, SS304	0
Outer Body	Black, RAL9011	Black, RAL9011	Black, RAL9011	Black, RAL9011	Black, RAL9011
Interior	SS430	SS430	SS430	SS430	SS430
Castors/Feet	10 adjustable feet	10 adjustable feet	10 adjustable feet	10 adjustable feet	10 adjustable feet
Lock	Y	Y	Y	Y	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	350	350	350	350	350
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	172	177	182	187	192
Net Weight, kg	162	167	172	177	182
Noise Level dbA	42	42	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a	R134a
Charge, g	190	190	190	190	190
Internal Light	LED	LED	LED	LED	LED

» KEG Coolers



- CKC2**
- Ventilated cooling
 - 1 Solid doors
 - 2 x 20 l. KEG capacity
 - Stainless steel interior
 - Adjustable feet



- CKC4**
- Ventilated cooling
 - 1 Solid doors
 - 4 x 20 l. KEG capacity
 - 1 x 50 l. KEG capacity
 - Stainless steel interior
 - Adjustable feet

Technical specifications

Model	CKC2	CKC4	CKC6	CKC8
Climate Class	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	99	190	270	362
KEG 20 l.	2	4	6	8
KEG 50 l.	-	1	1	2
External Dimensions, WxDxH	555X590X860	880X590X860	1110X590X860	1350X590X860
Internal Dimensions, WxDxH	270X500X730	520X500X730	735X500X730	990X500X730
Doors	1 hinged solid	1 hinged solid	2 hinged solid	2 hinged solid
Shelves/Baskets	-	-	-	-
Outer Body	Black, RAL9011	Black, RAL9011	Black, RAL9011	Black, RAL9011
Interior	SS304	SS304	SS304	SS304
Castors/Feet	4 adjustable feet	6 adjustable feet	6 adjustable feet	8 adjustable feet
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	250	250	250	250
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	63	80	93	104
Net Weight, kg	48	63	73	83
Noise Level dbA	45	45	45	45
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	120	150	150	150
Internal Light	N	N	N	N

